Indicator Inks FS0007/FS0008 (Aerosol)

SAAS Automotive Pty Ltd

Chemwatch: **64-8014** Version No: **3.1.1.1**

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 3

Issue Date: **03/08/2016**Print Date: **03/08/2016**S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

| Product name | Indicator Inks FS0007/FS0008 (Aerosol) |
|-------------------------------|--|
| Synonyms | Not Available |
| Proper shipping name | AEROSOLS |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| Relevant | identified |
|----------|------------|
| | uses |

Application is by spray atomisation from a hand held aerosol pack Printing ink.

Details of the supplier of the safety data sheet

| Registered company name | SAAS Automotive Pty Ltd |
|-------------------------|--|
| Address | 25 Metrolink Circuit – West Campbellfield VIC 3061 Australia |
| Telephone | +61 3 9930 0100 |
| Fax | Not Available |
| Website | www.shopsaas.com |
| Email | Not Available |

Emergency telephone number

| Association / Organisation | Not Available |
|-----------------------------------|---------------|
| Emergency telephone numbers | Not Available |
| Other emergency telephone numbers | Not Available |

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

| Poisons Schedule | S6 |
|-------------------------------|---|
| Classification ^[1] | Aerosols Category 1, Acute Toxicity (Oral) Category 4, Acute Toxicity (Dermal) Category 4, Reproductive Toxicity Category 1B |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI |

Label elements

GHS label elements







SIGNAL WORD

DANGER

Chemwatch: **64-8014** Page **2** of **12**

Version No: **3.1.1.1**

Indicator Inks FS0007/FS0008 (Aerosol)

Issue Date: **03/08/2016**Print Date: **03/08/2016**

Hazard statement(s)

| H222 | Extremely flammable aerosol. |
|--------|---|
| H302 | Harmful if swallowed. |
| H312 | Harmful in contact with skin. |
| H360 | May damage fertility or the unborn child. |
| AUH044 | Risk of explosion if heated under confinement |

Supplementary statement(s)

Not Applicable

Precautionary statement(s) Prevention

| P270 | Do not eat, drink or smoke when using this product. |
|------|---|
| P281 | Use personal protective equipment as required. |
| P251 | Pressurized container: Do not pierce or burn, even after use. |
| P211 | Do not spray on an open flame or other ignition source. |
| P210 | Keep away from heat/sparks/open flames/hot surfaces No smoking. |
| P201 | Obtain special instructions before use. |

Precautionary statement(s) Response

| P308+P313 | IF exposed or concerned: Get medical advice/attention. |
|-----------|--|
| P363 | Wash contaminated clothing before reuse. |
| P301+P312 | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water. |
| P330 | Rinse mouth. |

Precautionary statement(s) Storage

| P405 | Store locked up. |
|-----------|--|
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |

Precautionary statement(s) Disposal

| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

| mixtures | | |
|---------------|-----------|------------------------|
| CAS No | %[weight] | Name |
| Not Available | 38-40 | ketones |
| Not Available | 29-32 | glycol ether esters |
| Not Available | 10-12 | glycol ether |
| Not Available | 6-8 | vinyl resin |
| Various | 6-8 | acrylic resin |
| Not Available | 0.9-3.3 | dyes |
| 872-50-4 | 1.6-2 | N-methyl-2-pyrrolidone |
| Not Available | 1-1.4 | plasticiser |
| 115-10-6 | NotSpec. | dimethyl ether |

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact

If aerosols come in contact with the eyes:

▶ Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.

Chemwatch: 64-8014 Page 3 of 12 Issue Date: 03/08/2016 Version No: 3.1.1.1 Print Date: 03/08/2016

Indicator Inks FS0007/FS0008 (Aerosol)

| | Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
|--------------|---|
| Skin Contact | If solids or aerosol mists are deposited upon the skin: Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. DO NOT use solvents. Seek medical attention in the event of irritation. |
| Inhalation | If aerosols, fumes or combustion products are inhaled: Remove to fresh air. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor. |
| Ingestion | If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. |

Indication of any immediate medical attention and special treatment needed

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- ▶ Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- ▶ Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema.
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

ADVANCED TREATMENT

· Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

- ▶ Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- ▶ Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- · Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- ► Treat seizures with diazepam.
- ▶ Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

SMALL FIRE:

Water spray, dry chemical or CO2

LARGE FIRE:

Water spray or fog.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Chemwatch: 64-8014 Page 4 of 12 Issue Date: 03/08/2016 Version No: 3.1.1.1 Print Date: 03/08/2016

Indicator Inks FS0007/FS0008 (Aerosol)

| Fire Fighting | Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. |
|-----------------------|---|
| Fire/Explosion Hazard | Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition with violent container rupture. Combustion products include; carbon monoxide (CO) carbon dioxide (CO2) other pyrolysis products typical of burning organic material |

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| Minor Spills | Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Wipe up. If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. |
|--------------|---|
| Major Spills | Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses No smoking, naked lights or ignition sources. Increase ventilation. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

| Safe handling | ▶ Avoid all personal contact, including inhalation. |
|-------------------|--|
| | Wear protective clothing when risk of exposure occurs. |
| | ▶ Use in a well-ventilated area. |
| | ▶ Prevent concentration in hollows and sumps. |
| | ▶ DO NOT enter confined spaces until atmosphere has been checked. |
| | ► Avoid smoking, naked lights or ignition sources. |
| | Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject conter of can |
| | ▶ Store in original containers in approved flammable liquid storage area. |
| Other information | ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped. |
| | ▶ No smoking, naked lights, heat or ignition sources. |
| | ▶ Keep containers securely sealed. Contents under pressure. |
| | ▶ Store away from incompatible materials. |

| oonanions for sale st | orage, moraling any moonipationnes |
|-------------------------|--|
| Suitable container | ▶ Aerosol dispenser.▶ Check that containers are clearly labelled. |
| Storage incompatibility | ► Avoid reaction with oxidising agents |

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|---------------------------------|----------------------------|----------------------------|------------------------|------------------------|------------------|------------------|
| Australia Exposure Standards | N-methyl- 2-pyrrolidone | 1-Methyl- 2-pyrrolidone | 103 mg/m3 / 25 ppm | 309 mg/m3 / 75 ppm | Not Available | Sk |
| Australia Exposure Standards | dimethyl ether | Dimethyl ether | 760 mg/m3 / 400 ppm | 950 mg/m3 / 500 ppm | Not Available | Not Available |

EMERGENCY LIMITS

| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 |
|------------------------|---|-----------|----------|----------|
| N-methyl-2-pyrrolidone | Methyl 2-pyrrolidinone, 1-; (N-Methylpyrrolidone) | 10 ppm | 10 ppm | 10 ppm |
| N-methyl-2-pyrrolidone | Petroleum 50 thinner; (Paint thinner) | 5.5 ppm | 61 ppm | 370 ppm |
| dimethyl ether | Methyl ether; (Dimethyl ether) | 1,000 ppm | 1000 ppm | 7200 ppm |

| Ingredient | Original IDLH | Revised IDLH |
|------------------------|---------------|---------------|
| ketones | Not Available | Not Available |
| glycol ether esters | Not Available | Not Available |
| glycol ether | Not Available | Not Available |
| vinyl resin | Not Available | Not Available |
| acrylic resin | Not Available | Not Available |
| dyes | Not Available | Not Available |
| N-methyl-2-pyrrolidone | Not Available | Not Available |
| plasticiser | Not Available | Not Available |
| dimethyl ether | Not Available | Not Available |

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Personal protection











No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures: Eve and face protection

- Safety glasses with side shields.
- ▶ NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

Skin protection

Hands/feet protection

See Hand protection below

- ▶ No special equipment needed when handling small quantities.
- **▶ OTHERWISE:**
- ▶ For potentially moderate exposures:
- ▶ Wear general protective gloves, eg. light weight rubber gloves.
- ▶ For potentially heavy exposures:
- ▶ Wear chemical protective gloves, eg. PVC. and safety footwear.

Body protection

See Other protection below

No special equipment needed when handling small quantities.

Other protection

OTHERWISE: ▶ Overalls.

▶ Skin cleansing cream.

Version No: **3.1.1.1**

Indicator Inks FS0007/FS0008 (Aerosol)

Issue Date: **03/08/2016**Print Date: **03/08/2016**

- ► Eyewash unit.
- ▶ Do not spray on hot surfaces.
- The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.
- Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost. BRETHERICK: Handbook of Reactive Chemical Hazards.

Thermal hazards

Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Indicator Inks FS0007/FS0008 (Aerosol)

| Material | СРІ |
|----------------|-------|
| BUTYL | С |
| NATURAL RUBBER | С |
| NEOPRENE | С |
| PE/EVAL/PE | С |
| PVA | С |
| ##dimethyl | ether |

^{*} CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection

Type KAX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|---------------------------------------|-------------------------|-------------------------|---------------------------|
| up to 10 x ES | Air-line* | KAX-2 | KAX-PAPR-2 ^ |
| up to 20 x ES | - | KAX-3 | - |
| 20+ x ES | - | Air-line** | - |

* - Continuous-flow; ** - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Aerosols, in common with most vapours/ mists, should never be used in confined spaces without adequate ventilation. Aerosols, containing agents designed to enhance or mask smell, have triggered allergic reactions in predisposed individuals.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| Appearance | Various coloured highly flammable liquid with strong odour; dies not mix with water. | | |
|--|--|---|----------------|
| | | | |
| Physical state | Liquid | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Available | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Available |
| Initial boiling point and boiling range (°C) | 78.5-171 | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | -4 (TCC) | Taste | Not Available |
| Evaporation rate | Not Available | Explosive properties | Not Available |
| Flammability | HIGHLY FLAMMABLE. | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | 10.6 | Surface Tension (dyn/cm or mN/m) | Not Available |
| Lower Explosive Limit (%) | 1.1 | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | 1.3 @20C | Gas group | Not Available |

Page **7** of **12** Version No: 3.1.1.1

Indicator Inks FS0007/FS0008 (Aerosol)

Issue Date: 03/08/2016 Print Date: 03/08/2016

| Solubility in water (g/L) | Immiscible | pH as a solution (1%) | Not Available |
|---------------------------|---------------|-----------------------|---------------|
| Vapour density (Air = 1) | Not Available | VOC g/L | Not Available |

SECTION 10 STABILITY AND REACTIVITY

| Reactivity | See section 7 |
|--|--|
| Chemical stability | Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Indicator Inks

FS0007/FS0008

TOXICITY

| Inhaled | There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of high vapour concentrations of N-methyl-2-pyrrolidone (NMP) may produce mucous membrane irritation, headache, giddiness, mental confusion and nausea. Fatalities were not recorded following inhalation of 180-200 mg/m3 for 2 hours by mice and following a 6 hour exposure to saturated vapours by rats. Laboratory animals exposed to concentrations of 50 ppm for 8 hours daily for 20 days or 370 ppm for 6 hours daily for 10 days or showed no group or histographylacial shortmalities. |
|--------------|--|
| | days showed no gross or histopathological abnormalities WARNING:Intentional misuse by concentrating/inhaling contents may be lethal. Spray mist may produce discomfort |
| Ingestion | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Considered an unlikely route of entry in commercial/industrial environments |
| Skin Contact | The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives. Skin contact with the material may be harmful; systemic effects may result following absorption. Prolonged contact with N-methyl-2-pyrrolidone (NMP) reportedly causes severe dermatitis with redness, cracking, swelling, blisters and oedema. An instance of severe skin irritation after a few days work with NMP shows latex rubber gloves as giving insufficient protection. A review article casts doubts on reliability of animal single patch tests, i.e Draize tests. [Irritant Cutaneous Reaction to NMP, Contact Dermatitis 27: 148-150, 1992] Spray mist may produce discomfort Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Ketone vapours irritate the nose, throat and mucous membrane. High concentrations depress the central nervous system, causing headache, vertigo, poor concentration, sleep and failure of the heart and breathing. |
| Еуе | There is some evidence to suggest that this material can cause eye irritation and damage in some persons. Direct contact with the liquid N-methyl-2-pyrrolidone (NMP) may produce painful burning or stinging of the eyes and lids, watering and inflammation of the conjunctiva and temporary corneal clouding. Not considered to be a risk because of the extreme volatility of the gas. |
| Chronic | Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. The teratogenic potential, subchronic and long term inhalation toxicity of N-methyl-2-pyrrolidone (NMP has been studied in rats. No evidence of nephrotoxicity was seen. No carcinogenic effects were observed. Very high doses are embryotoxic to rats and mice. Reproductive effects have been reported in animals. |

IRRITATION

Chemwatch: 64-8014 Page 8 of 12 Issue Date: 03/08/2016
Version No: 3.1.1.1 Print Date: 03/08/2016

Indicator Inks FS0007/FS0008 (Aerosol)

| | Dermal (Rat) LD50: 1800 mg/kg* ^[2] | Not Available | |
|----------------|--|---------------------------------|--|
| | Inhalation (Mouse) LC50: 3360 mg/l/4h*[2] | | |
| | Inhalation (Rat) LC50: 2400 mg/l/4h*[2] | | |
| (Aerosol) | Oral (Mouse) LD50: 1200 mg/kg* ^[2] | | |
| | Oral (Rabbit) LD50: 320 mg/kg* ^[2] | | |
| | Oral (Rat) LD50: 560 mg/kg* ^[2] | | |
| | | 1 | |
| acrylic resin | TOXICITY | IRRITATION | |
| acrylic resili | Not Available | Not Available | |
| | TOXICITY | IRRITATION | |
| N-methyl- | dermal (rat) LD50: >5000 mg/kg ^[1] | *[Manufacturer] | |
| 2-pyrrolidone | Inhalation (rat) LC50: 8300 ppm/4hr ^[2] | Eye (rabbit): 100 mg - moderate | |
| | Oral (rat) LD50: 3914 mg/kg ^[2] | | |
| | TOXICITY | IRRITATION | |
| dimethyl ether | Inhalation (rat) LC50: 309 mg/L/4hr ^[2] | Nil reported | |
| Legend: | Value obtained from Europe ECHA Registered Substances | | |
| | Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | | |

No significant acute toxicological data identified in literature search.

ACRYLIC RESIN

CAUTION: The chronic health effects of acrylic monomers are under review.

Use good occupational work practices to avoid personal contact.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dysonea, cough and mucus production.

for N-methyl-2-pyrrolidone (NMP):

Acute toxicity: In rats, NMP is absorbed rapidly after inhalation, oral, and dermal administration, distributed throughout the organism, and eliminated mainly by hydroxylation to polar compounds, which are excreted via urine. About 80% of the administered dose is excreted as NMP and NMP metabolites within 24 h. A probably dose-dependent yellow coloration of the urine in rodents is observed. The major metabolite is 5-hydroxy-*N*-methyl-2-pyrrolidone.

Studies in humans show comparable results. Dermal penetration through human skin has been shown to be very rapid. NMP is rapidly biotransformed by hydroxylation to 5-hydroxy-*N*-methyl-2-pyrrolidone, which is further oxidized to *N*-methylsuccinimide; this intermediate is further hydroxylated to 2-hydroxy-*N*-methylsuccinimide. These metabolites are

all colourless. The excreted amounts of NMP metabolites in the urine after inhalation or oral intake represented about 100% and 65% of the administered doses, respectively.

NMP has a low potential for skin irritation and a moderate potential for eye irritation in rabbits. Repeated daily doses of 450 mg/kg body weight administered to the skin caused painful and severe haemorrhage and eschar formation in rabbits. These adverse effects have not been seen in workers occupationally exposed to pure NMP, but they have been observed after dermal exposure to NMP used in cleaning processes. No sensitisation potential has been observed.

In acute toxicity studies in rodents, NMP showed low toxicity. Uptake of oral, dermal, or inhaled acutely toxic doses causes functional disturbances and depressions in the central nervous system. Local irritation effects were observed in the respiratory tract when NMP was inhaled and in the pyloric and gastrointestinal tracts after oral administration. In humans, there was no irritative effect in the respiratory system after an 8-h exposure to 50 mg/m3.

Repeat dose toxicity: There is no clear toxicity profile of NMP after multiple administration. In a 28-day dietary study in rats, a compound-related decrease in body weight gain was observed in males at 1234 mg/kg body weight and in females at 2268 mg/kg body weight. Testicular degeneration and atrophy in males and thymic atrophy in females were observed at these dose levels. The no-observed-adverse-effect level (NOAEL) was 429 mg/kg body weight in males and 1548 mg/kg body weight in females. In a 28-day intubation study in rats, a dose-dependent increase in relative liver and kidney weights and a decrease in lymphocyte count in both sexes were observed at 1028 mg/kg body weight. The NOAEL in this study was 514 mg/kg body weight. In another rat study, daily dietary intake for 90 days caused decreased body weights at doses of 433 and 565 mg/kg body weight in males and females, respectively. There were also neurobehavioural effects at these dose

N-METHYL-2-PYRROLIDONE

Chemwatch: 64-8014 Page 9 of 12

Version No: 3.1.1.1

Indicator Inks FS0007/FS0008 (Aerosol)

Issue Date: **03/08/2016**Print Date: **03/08/2016**

levels. The NOAELs in males and females were 169 and 217 mg/kg body weight, respectively.

The toxicity profile after exposure to airborne NMP depends strongly on the ratio of vapour to aerosol and on the area of exposure (i.e., head-only or whole-body exposure). Because of higher skin absorption for the aerosol, uptake is higher in animals exposed to aerosol than in those exposed to vapour at similar concentrations. Studies in female rats exposed head only to 1000 mg/m3 showed only minor nasal irritation, but massive mortality and severe effects on major organs were observed when the females were whole-body exposed to the same concentration of coarse droplets at high relative humidity. Several studies in rats following repeated exposure to NMP at concentrations between 100 and 1000 mg/m3 have shown systemic toxicity effects at the lower dose levels. In most of the studies, the effects were not observed after a 4-week observation period.

In rats, exposure to 3000 mg NMP/m3 (head only) for 6 h/day, 5 days/week, for 13 weeks caused a decrease in body weight gain, an increase in erythrocytes, haemoglobin, haematocrit, and mean corpuscular volume, decreased absolute testis weight, and cell loss in the germinal epithelium of the testes. The NOAEL was 500 mg/m3.

There are no data in humans after repeated-dose exposure.

Carcinogenicity: NMP did not show any clear evidence for carcinogenicity in rats exposed to concentrations up to 400 mg/m3 in a long-term inhalation study.

Genotoxicity: The mutagenic potential of NMP is weak. Only a slight increase in the number of revertants was observed when tested in a *Salmonella* assay with base-pair substitution strains. NMP has been shown to induce aneuploidy in yeast *Saccharomyces cerevisiae* cells. No investigations regarding mutagenicity in humans were available.

Reproductive toxicity: In a two-generation reproduction study in rats, whole-body exposure of both males and females to 478 mg/m3 of NMP vapour for 6 h/day, 7 days/week, for a minimum of 100 days (pre-mating, mating, gestation, and lactation periods) resulted in a 7% decrease in fetal weight in the F1 offspring. A 4-11% transient, non-dose-dependent decrease was observed in the average pup weight at all exposure levels tested (41, 206, and 478 mg/m3).

Developmental toxicity: When NMP was administered dermally, developmental toxicity was registered in rats at 750 mg/kg body weight. The observed effects were increased preimplantation losses, decreased fetal weights, and delayed ossification. The NOAEL for both developmental effects and maternal toxicity (decreased body weight gain) was 237 mg/kg body weight. Inhalation studies in rats (whole-body exposure) demonstrated developmental toxicity as increased preimplantation loss without significant effect on implantation rate or number of live fetuses at 680 mg/m3 and behavioural developmental toxicity at 622 mg/m3. In an inhalation study (whole-body exposure), the NOAEL for maternal effects was 100 mg/m3, and the NOAEL for developmental effects was 360 mg/m3.

A tolerable inhalation concentration, 0.3 mg/m3, based on mortality and organ damage, is expected to be protective against any possible reproductive toxicity. Similarly, an oral tolerable intake of 0.6 mg/kg body weight per day, based on a 90-day study, is expected to provide adequate protection against possible reproductive effects. Because of non-existent data on the exposure of the general population and very limited information on occupational exposure, no meaningful risk characterisation can be performed

| Acute Toxicity | ~ | Carcinogenicity | 0 |
|-----------------------------------|----------|-----------------------------|----------|
| Skin Irritation/Corrosion | 0 | Reproductivity | ✓ |
| Serious Eye Damage/Irritation | 0 | STOT - Single Exposure | 0 |
| Respiratory or Skin sensitisation | 0 | STOT - Repeated Exposure | 0 |
| Mutagenicity | 0 | Aspiration Hazard | 0 |

Leaend:

- 🗶 Data available but does not fill the criteria for classification
- ✓ Data required to make classification available
- O Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

| Ingredient | Endpoint | Test Duration (hr) | Species | Value | Source |
|----------------------------|----------|--------------------|-------------------------------|-------------|--------|
| N-methyl- 2-pyrrolidone | EC50 | 48 | Crustacea | ca.4897mg/L | 1 |
| N-methyl- 2-pyrrolidone | EC50 | 384 | Crustacea | 133.481mg/L | 3 |
| N-methyl- 2-pyrrolidone | LC50 | 96 | Fish | 464mg/L | 1 |
| N-methyl- 2-pyrrolidone | NOEC | 504 | Crustacea | 12.5mg/L | 2 |
| N-methyl- 2-pyrrolidone | EC50 | 72 | Algae or other aquatic plants | >500mg/L | 2 |
| dimethyl ether | NOEC | 48 | Crustacea | >4000mg/L | 1 |
| dimethyl ether | EC50 | 384 | Crustacea | 46.027mg/L | 3 |
| dimethyl ether | LC50 | 96 | Fish | 200.592mg/L | 3 |

Chemwatch: 64-8014 Page 10 of 12 Issue Date: 03/08/2016 Version No: 3.1.1.1 Print Date: 03/08/2016

Indicator Inks FS0007/FS0008 (Aerosol)

| dimethyl ether | EC50 | 48 | Crustacea | >4400.0mg/L | 2 |
|----------------|--------------------|---|-------------------------------|-------------|-----------|
| dimethyl ether | EC50 | 96 | Algae or other aquatic plants | 154.917mg/L | 2 |
| Legend: | 3. EPIWIN Suite V3 | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor | | | 5. ECETOC |

DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|------------------------|-------------------------|------------------|
| N-methyl-2-pyrrolidone | LOW | LOW |
| dimethyl ether | LOW | LOW |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------------------|--------------------|
| N-methyl-2-pyrrolidone | LOW (BCF = 0.16) |
| dimethyl ether | LOW (LogKOW = 0.1) |

Mobility in soil

| Ingredient | Mobility |
|------------------------|--------------------|
| N-methyl-2-pyrrolidone | LOW (KOC = 20.94) |
| dimethyl ether | HIGH (KOC = 1.292) |

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- ▶ Reuse
- Recycling
- ► Disposal (if all else fails)

Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ► Consult State Land Waste Management Authority for disposal.
- ▶ Discharge contents of damaged aerosol cans at an approved site.
- ▶ Allow small quantities to evaporate.
- ► DO NOT incinerate or puncture aerosol cans.
- ▶ Bury residues and emptied aerosol cans at an approved site.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Land transport (ADG)

Chemwatch: 64-8014 Page 11 of 12 Issue Date: 03/08/2016 Version No: 3.1.1.1 Print Date: 03/08/2016

Indicator Inks FS0007/FS0008 (Aerosol)

| UN number | 1950 | |
|------------------------------|--|--|
| UN proper shipping name | AEROSOLS | |
| Transport hazard class(es) | Class 2.1 Subrisk Not Applicable | |
| Packing group | Not Applicable | |
| Environmental hazard | Not Applicable | |
| Special precautions for user | Special provisions 63 190 277 327 344 Limited quantity 1000ml | |

Air transport (ICAO-IATA / DGR)

| • • | <u> </u> | | | |
|------------------------------|--|---------------------------------------|------------------------------|--|
| UN number | 1950 | | | |
| UN proper shipping name | Aerosols, flammable; Aerosols, flammable (engine starting fluid) | | | |
| Transport hazard | ICAO/IATA Class | 2.1 | | |
| Transport hazard class(es) | ICAO / IATA Subrisk | Not Applicable | | |
| 0.000(00) | ERG Code | 10L | | |
| Packing group | Not Applicable | | | |
| Environmental hazard | Not Applicable | | | |
| | Special provisions | | A145A167A802; A1A145A167A802 | |
| | Cargo Only Packing Instructions | | 203 | |
| | Cargo Only Maximum Qty / Pack | | 150 kg | |
| Special precautions for user | Passenger and Cargo Packing Instructions | | 203; Forbidden | |
| 101 4301 | Passenger and Cargo Maximum Qty / Pack | | 75 kg; Forbidden | |
| | Passenger and Cargo | Limited Quantity Packing Instructions | Y203; Forbidden | |
| | Passenger and Cargo | Limited Maximum Qty / Pack | 30 kg G; Forbidden | |

Sea transport (IMDG-Code / GGVSee)

| UN number | 1950 | | |
|---------------------------------|---|--|--|
| UN proper shipping name | AEROSOLS | | |
| Transport hazard class(es) | IMDG Class 2.1 IMDG Subrisk Not Applicable | | |
| Packing group | Not Applicable | | |
| Environmental hazard | Not Applicable | | |
| Special precautions for user | EMS Number F-D, S-U Special provisions 63 190 277 327 344 959 Limited Quantities 1000ml | | |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ACRYLIC RESIN(VARIOUS) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

N-METHYL-2-PYRROLIDONE(872-50-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Indicator Inks FS0007/FS0008 (Aerosol)

Print Date: 03/08/2016

Australia Exposure Standards Australia Inventory of Chemical Substances (AICS) Australia Hazardous Substances Information System - Consolidated Lists

DIMETHYL ETHER(115-10-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists International Air Transport Association (IATA) Dangerous Goods Regulations

- Prohibited List Passenger and Cargo Aircraft

| National Inventory | Status |
|----------------------------------|--|
| Australia - AICS | Y |
| Canada - DSL | Υ |
| Canada - NDSL | N (dimethyl ether; N-methyl-2-pyrrolidone) |
| China - IECSC | Υ |
| Europe - EINEC / ELINCS / NLP | Υ |
| Japan - ENCS | Υ |
| Korea - KECI | Υ |
| New Zealand - NZIoC | Υ |
| Philippines - PICCS | Υ |
| USA - TSCA | Υ |
| Legend: | Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

| Name | CAS No |
|------------------------|-----------------------|
| N-methyl-2-pyrrolidone | 872-50-4, 26138-58-9 |
| dimethyl ether | 115-10-6, 157621-61-9 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.